



0000 00 00000000 00000 000 .000 0000000 000000 00000 0000 00 000 58W 000000 000 000 00000 00000 00
 00 (IP-Phone) 00000 000 00000000 0 0000 000 00000000000 0000000000000 000000000 00000 00000 00000
 00000 000000 000 000000 000 00 00000000 0000000 000 00000 00 00000 00 00000 000 000 00000 00 .000 000000
 000000 0000000 0000000 .000 00 000000 00 000 250 000000 00 000000 000000 000000 00 000 000000 Extend
 000000 000000 00000 0000000000 00 000000 00000 000 0000000 00 00000 00000 0000000 00 00 000000000000 00000
 00000 000000 000 00000 00 000000 00000 0 00000 00000000 000000 0 000000000 0000000 00000 00000 00000 00 00
 .00000 0000000 00000 00000 0000 000 000 0000000 0 00 000000 00000 00000 00000 0000 00000 000 000000

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

[illegible]

PoE 58W

PoE IEEE802.3at IEEE802.3af 4 1 58W . 30W .

250

250 .

.

IEEE 802.3 IEEE 802.3u IEEE 802.3x IEEE 802.3af IEEE 802.3at	
Link/Act, PoE Status, Power, 1000M	LED
4x10/100Base-TX RJ45 Ports(Data/Power)/ 1x10/100/1000Base-T RJ45 (Port(Data	
Port 1 to Port 4 support standard IEEE802.3at/af power(maximum power for each port is 30W) PoE power type is end-span(1245+, 3678- line pair) in full configuration<63W PoE Max Power Supply58W	PoE
(100mm*100mm*26mm (W × D × H	

: 21:53 - 07/04/1399

<https://www.shabakeh-mag.com/networking-technology/17010/%D8%A2%D8%B4%D9%86%D8%A7%DB%8C%DB%8C-%D8%A7%D8%AC%D9%85%D8%A7%D9%84%DB%8C-%D8%A8%D8%A7-%D8%B3%D9%88%DB%8C%DB%8C%DA%86-5-%D9%BE%D9%88%D8%B1%D8%AA-s1105-4-pwr-%D8%B4%D8%B1%DA%A9%D8%AA-%D8%A2%DB%8C%E2%80%8C%D9%BE%DB%8C%E2%80%8C%DA%A9%D8%A7%D9%85>