禪

[illegible]

[illegible]



[illegible]

[illegible]

[illegible]

[illegible] ownCloud [illegible]

[illegible]

[illegible]

[illegible]

netstat -npl

[illegible]

systemctl list-unit-files --type=service | grep enabled



```
[swapnil@arch ~]$ sudo systemctl list-unit-files --type=service | grep enable
d
[sudo] password for swapnil:
dbus-org.freedesktop.NetworkManager.service enabled
dbus-org.freedesktop.nm-dispatcher.service  enabled
display-manager.service                     enabled
getty@.service                              enabled
NetworkManager-dispatcher.service           enabled
NetworkManager.service                      enabled
sddm.service                                enabled
vboxservice.service                         enabled
[swapnil@arch ~]$ 
```

[illegible] systemctl [illegible]

systemctl disable service_name

[illegible]

[illegible]

[illegible] Root [illegible]

[illegible] ssh [illegible] ssh [illegible] ssh [illegible].

[illegible] Red Hat/CentOS [illegible] useradd [illegible] Ubuntu/Debian [illegible] adduser [illegible].

[illegible] Red Hat/CentOS [illegible] (swapnil [illegible]):

```
useradd swapnil
```

[illegible]:

```
passwd swapnil
```

[illegible] sudo [illegible]:

```
EDITOR=nano visudo
```

[illegible]

```
# %wheel ALL=(ALL) ALL
```



```
  GNU nano 2.4.2              File: /etc/sudoers.tmp

##
## Runas alias specification
##

##
## User privilege specification
##
root ALL=(ALL) ALL

## Uncomment to allow members of group wheel to execute any command
 %wheel ALL=(ALL) ALL

## Same thing without a password
# %wheel ALL=(ALL) NOPASSWD: ALL

## Uncomment to allow members of group sudo to execute any command
# %sudo ALL=(ALL) ALL

## Uncomment to allow any user to run sudo if they know the password
## of the user they are running the command as (root by default).
# Defaults targetpw  # Ask for the password of the target user
# ALL ALL=(ALL) ALL  # WARNING: only use this together with 'Defaults targetpw'

^G Get Help    ^O Write Out   ^W Where Is    ^K Cut Text    ^J Justify     ^C Cur Pos
^X Exit        ^R Read File   ^\ Replace     ^U Uncut Text  ^T To Spell    ^_ Go To Line
```

[illegible]. [illegible] # [illegible] ([illegible]) [illegible]:

```
%wheel ALL=(ALL) ALL
```

[illegible]. [illegible] wheel [illegible]:

```
# usermod -aG wheel swapnil
```

[illegible]:

```
adduser swapnil
```

[illegible]. [illegible] sudo [illegible]:

```
gpasswd -a swapnil sudo
```

[illegible] sudo [illegible]. [illegible].

[illegible] root

[illegible] root [illegible]. [illegible] ssh [illegible]. [illegible] sshd [illegible]:

```
nano /etc/ssh/sshd_conf
```

[illegible]:

```
#PermitRootLogin no
```

[illegible]:

```
service ssh restart
```

[illegible]:

```
systemctl restart sshd
```

[illegible]: [illegible]. [illegible] ssh [illegible]. [illegible].

[illegible]

[illegible] sshd [illegible]. [illegible].

[illegible]

[illegible] sshd_config [illegible] sudo [illegible]:

```
sudo nano /etc/ssh/sshd_conf
```

[illegible]:

```
#Port 22
```

[illegible] 1977 [illegible]:

```
Port 1977
```

[illegible] sshd [illegible]:

```
ssh -p{port_number}@server_IP
```

[illegible]:

```
ssh -p1977
```

This e-mail address is being protected from spambots. You need JavaScript enabled to view it

[illegible].

[illegible]

[illegible] ssh [illegible]. [illegible] ssh [illegible].

[illegible] ssh [illegible]:

```
ssh-keygen - t rsa
```



```
[swapnil@arch ~]$ ssh-keygen -t rsa
Generating public/private rsa key pair.
Enter file in which to save the key (/home/swapnil/.ssh/id_rsa):
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/swapnil/.ssh/id_rsa.
Your public key has been saved in /home/swapnil/.ssh/id_rsa.pub.
The key fingerprint is:
SHA256:8ml1v6ROAs4/6LRrFxeQC+VDYSP6CGcY5uRiVf98b34 swapnil@arch
The key's randomart image is:
+---[RSA 2048]----+
|    =.. ..*o     |
|   * o o.=o.     |
|  o = + ..oo     |
| . . + o o...    |
|      o S + o.   |
|       = +.o.o   |
|        B..o. =  |
|       ooooo = .E|
|       o+o.oo o. |
+----[SHA256]-----+
[swapnil@arch ~]$ 
```

[illegible]

```
cat ~/.ssh/id_rsa.pub | ssh -p 1977 swapnil@remote-server ";mkdir -p ~/.ssh && cat >> ~/.ssh/authorized_keys"
```

[illegible]

[illegible] sshd_config [illegible]

```
#PasswordAuthentication yes
```

[illegible] yes [illegible] no [illegible] sshd [illegible]

[illegible] ssh [illegible]

[illegible]

[illegible]

[illegible].

================================

[illegible]:

[illegible]!

Xeon E7 v4 [illegible]

[illegible]!

AFR@NET
Internet & E-Comme

[illegible]

[illegible]

Q
W
S
X
A
Z

[illegible]

[illegible]

[illegible]

[illegible]:
[illegible]
[illegible]:
[illegible]
[illegible]:
[illegible]
[illegible]:
12:00 - 07/06/1395
[illegible]:
[illegible] - [illegible] - [illegible] - [illegible] - [illegible]

[illegible]
[illegible]: https://www.shabakeh-mag.com/tricks/network-tricks/4260/%DA%86%DA%AF%D9%88%D9%86%D9%87-%D8%B3%D8%B1%D9%88%D8%B1-%D9%84%DB%8C%D9%86%D9%88%DA%A9%D8%B3-%D8%A7%D9%85%D9%86%E2%80%8E%D8%AA%D8%B1%DB%8C-%D8%AF%D8%A7%D8%B4%D8%AA%D9%87-%D8%A8%D8%A7%D8%B4%DB%8C%D9%85%D8%9F