[illegible]

[illegible]

[illegible] Clone [illegible] Build [illegible]

[illegible]

[illegible] (Source Code) [illegible] (Open Source) [illegible]

[illegible]

[illegible]

[illegible] (Codebase) [illegible] (Git) [illegible] (Repository) [illegible]

[illegible]

راهنمای جامع آرشیو کردن فایل ها در سیستم عامل

[illegible]

[illegible]

[illegible] 1398 [illegible] 100 [illegible] GitLab [illegible] BitBucket [illegible]

[illegible]

[illegible]

[illegible]

[illegible]

(Readme) [illegible]

[illegible] ReadMe [illegible] readme [illegible] README [illegible] md. [illegible] Atom [illegible] README.md [illegible] readme [illegible] readme [illegible] md. [illegible] (Markdown) [illegible] 1 [illegible] readme [illegible].



Building

- Linux
- macOS
- Windows

Discussion

- Discuss Atom on our forums
- Chat about Atom on our Slack team -- instructions for joining

License

MIT

[illegible] readme [illegible] ([illegible]) [illegible]

[illegible]

[illegible] (Clone) [illegible] Atom Editor [illegible] ReadMe [illegible] readMe [illegible] Development [illegible] building from source [illegible] Atom Editor [illegible] https://boxes.thomasjensen.com/build.html [illegible] (2 [illegible]).


License

Boxes is free software under the GNU General Public License, version 2 (GPLv2).

Development

The website has information on building from source, testing, and contributing to the sou
Boxes has received support from many contributors over the years, and continues to be
Many thanks for that!

Running it

Try if boxes works by typing `echo foo | boxes` on the command line. It should give you

```
/*******/
/* foo */
/*******/
```

[illegible]

[illegible] Building on Linux [illegible] make [illegible] Bison [illegible] C compiler [illegible] Flex [illegible] (Dependencies) [illegible] (3 [illegible]).


Building on Linux / UNIX

Just unzip the source archive or clone the GitHub repo. Make sure you have your C compiler installed, including Flex and Bison.

The location of the system-wide config file is compiled in, so if you don't like it's default location, you can edit the top level *Makefile* and change the value of

[illegible] Atom Editor [illegible].

[illegible] GCC

[illegible]:

sudo apt-get install git

[illegible]:

sudo apt-get install flex

[illegible] bison [illegible]:

sudo apt-get install bison

[illegible] make [illegible]:

sudo apt-get install make

[illegible] Atom Editor [illegible]:

sudo dnf install flex

sudo dnf install bison

sudo dnf install make

[illegible] Manjaro [illegible] (GCC) [illegible]:

sudo pacman -Syu gcc

```
sudo pacman -Syu flex
sudo pacman -Syu bison
```

[illegible]

[illegible] Clone or download [illegible] Download ZIP [illegible] 4).



Use Git or checkout with SVN using the web URL.

https://github.com/ascii-boxes/boxes.

[illegible] CD [illegible] git clone [illegible] Ctrl+Shift+V [illegible] 5).



```
dave@howtogeek:~/work$ git clone https://github.com/ascii-boxes/boxes.
git 
```

[illegible] 6).



```
dave@howtogeek:~/work$ git clone https://github.com/ascii-boxes/boxes.
git
Cloning into 'boxes'...
remote: Enumerating objects: 36, done.
remote: Counting objects: 100% (36/36), done.
remote: Compressing objects: 100% (27/27), done.
remote: Total 2405 (delta 15), reused 21 (delta 9), pack-reused 2369
Receiving objects: 100% (2405/2405), 1.28 MiB | 805.00 KiB/s, done.
Resolving deltas: 100% (1467/1467), done.
dave@howtogeek:~/work$ 
```

[illegible] boxes [illegible] 7).



```
dave@howtogeek:~/work/boxes$ ls
boxes-config           boxes.spec  LICENSE    README.Win32.md  tools
boxes-pkg.openwrt      boxes.vim   Makefile   src
boxes.portable.nuspec  doc         README.md  test
dave@howtogeek:~/work/boxes$ 
```

[illegible].

[illegible]

[illegible] Atom Editor [illegible] make [illegible]. [illegible] makefile [illegible] make [illegible]. [illegible] make [illegible]. [illegible] Atom Editor [illegible]. [illegible] && [illegible].

```
make && make test
```

[illegible].

[illegible]

[illegible] /usr/bin [illegible]. [illegible] CD [illegible]. [illegible] filesystem [illegible]... [illegible]. [illegible] Atom Editor [illegible]. [illegible] sudo [illegible].

[illegible] (man page) [illegible] man1 [illegible]:

```
sudo cp doc/boxes.1 /usr/share/man/man1
```

[illegible] /usr/share/: [illegible]:

```
sudo cp boxes-config /usr/share/boxes
```

[illegible] /usr/bin [illegible]:

```
sudo cp src/boxes /usr/bin
```

[illegible]

[illegible] Boxes [illegible]. [illegible]:

Man boxes

[illegible] boxes [illegible] (8 [illegible]).



```
boxes(1)                 General Commands Manual                 boxes(1)

NAME
       boxes - text mode box and comment drawing filter

SYNOPSIS
       boxes  [-hlmrv] [-a format] [-d design] [-f file] [-i indent]
       [-k bool] [-p pad] [-s size] [-t tabopts] [infile [outfile]]

DESCRIPTION
       Boxes is a text filter which can draw any kind of box  around
       its input text. Box design choices range from simple boxes to
       complex ASCII art. A box can also be  removed  and  repaired,
       even  if  it  has  been  badly damaged by editing of the text
       inside. Since boxes may be open on any side, boxes  can  also
       be  used  to create regional comments in any programming lan-
       guage.  New box designs of all sorts can easily be added  and
       shared by appending to a configuration file.

       boxes  is  a  command line tool, but also integrates with any
 Manual page boxes(1) line 1 (press h for help or q to quit)
```

[illegible] Manual [illegible] Q [illegible]. [illegible]:

echo How-To Geek | boxes

[illegible] 9 [illegible].



```
dave@howtogeek:~$ echo How-To Geek | boxes
/***************/
/* How-To Geek */
/***************/
dave@howtogeek:~$ 
```

[illegible] boxes [illegible]

[illegible] boxes [illegible]. [illegible] -d [illegible].

[illegible] 10 [illegible].

echo How-To Geek | boxes -d whirly

echo How-To Geek | boxes -d c-cmt2



```
dave@howtogeek:~$ echo How-To Geek | boxes -d whirly
 .+"+.+"+.+"+.
( How-To Geek )
 )           (
(             )
 "+.+"+.+"+.+"
dave@howtogeek:~$ echo How-To Geek | boxes -d c-cmt2
/*
 *  How-To Geek
 */
dave@howtogeek:~$ 
```

[illegible]

[illegible]

[illegible]. [illegible]:

1.[illegible].

2. [illegible].

3. [illegible]

4. [illegible] make [illegible].

6. [illegible].

[illegible]. [illegible] Contact Us [illegible].

[illegible]:

[illegible]

[illegible]:

[illegible]

[illegible]

[illegible]:

05:25 - 09/09/1398

[illegible]:

[illegible] - [illegible] - [illegible]

[illegible]

[illegible]:https://www.shabakeh-mag.com/workshop/16250/%DA%86%DA%AF%D9%88%D9%86%D9%87-%D8%B3%D9%88%D8%B1%D8%B3%E2%80%8C%DA%A9%D8%AF-%D8%A8%D8%B1%D9%86%D8%A7%D9%85%D9%87%E2%80%8C%D9%87%D8%A7-%D8%B1%D8%A7-%D8%B1%D9%88%DB%8C-%D9%84%DB%8C%D9%86%D9%88%DA%A9%D8%B3-%D8%A8%D9%87-%DB%8C%DA%A9-%D9%81%D8%A7%DB%8C%D9%84-%D8%A7%D8%AC%D8%B1%D8%A7%DB%8C%DB%8C-%D8%AA%D8%A8%D8%AF%DB%8C%D9%84-%DA%A9%D9%86%DB%8C%D9%85%D8%9F